

Cabinet Lift Series

Stay Lift Systems Cushion Closing



Description

Introducing a innovative cushion closing lift system - a seamless blend of functionality and design. Experience the perfect harmony of smooth and silent operation and contemporary design, ensuring a closure every time. Where convenience meets style.

Features

- Maximise the cabinet storage space
- Cushion closing
- Adjustable to the weight of your door
- Cabinet heights between 160mm - 400mm
- Minimum cabinet depth of 100mm
- Quick and simple installation with quick disconnect
- Elegant chrome finish

Applications



- Kitchen & Bath Cabinets
- Store Fixtures
- Architectural Millwork
- Office Furniture
- Medical Equipment Storage

Cabinet Lift Series



Stay Lift Systems Cushion Closing

Cabinet and Door Mounting Plate Locations



Use 2 chipboard screws (609.1x00) for wooden fronts.

Use 2 counter sunk self tapping screws for wide alu frames.

FAo	Upper front overlay
SFA	Front overlay of the side panel
MD	Mounting plate spacing
K	Cranking of hinge arm
	Straight hinge arm – 0 mm
	Cranked hinge arm – 9.5 mm
	Double cranked arm – 18 mm
()	Internal cabinet depth 100 mm

$H = 137 + MD + K + SOB$	
MD	Mounting plate spacing
K	Cranking of hinge arm
	Straight hinge arm – 0 mm
	Cranked hinge arm – 9.5 mm
	Double cranked arm – 18 mm
SOB	Top panel thickness
()	Internal cabinet depth 100 mm

– Standard hinge and plate drilling

Ordering

Cabinet Door Lift Mechanism Stay Lift

Part Number: 240-1619

Face Frame Mounting Plate Clip-On

Part Number: 240-1637

Note: To be used in conjunction with two soft closing hinges and plates.

FORCE FACTOR

Cabinet height in mm X Door Weight in Kgs

(include handle weight)

1 PCS	400-1600
2 PCS	800-3200



5775 McLaughlin Rd, Mississauga, Ontario L5R 3P7
TF: 1.866.200.0564 | T: 905.625.0564

inquiries@comtradsourcing.com | www.comtradsourcing.com